

ROTADAIRON®

SD 7000

SELF-PROPELLED SEEDING MACHINE

WEEDING

RAKING

SOIL
PREPARATION

SEEDING

OVERSEEDING

DETHATCHING-
SPIKING

MULCHING



MADE IN FRANCE

SELF-PROPELLED SEEDING MACHINE

SD 700

Functions of the seeder SD 700

The Rotadairon® SD 700 is a self-propelled seeding machine designed for precision seeding, seed burial and field filling.

The Rotadairon® SD 700 can be used to sow the majority of grass varieties such as bluegrass, red fescue, ray grass, etc...

Reliable, handy and efficient, it allows you to sow quickly and effortlessly.

The metal mesh roller, at the front, wafts the soil. Then the seed drill deposits the seeds. Then the rotor claws the soil. Finally the smooth roller at the back compacts the soil ideally to obtain a good germination and avoid the marking of the steps of the user.

The Rotadairon® SD 700 is driven by the rear packer roller.






Quality of service

A large stock of spare parts is permanently maintained at our factory. Our partners have online tools and quick access to manufacturer information.

Maintain the quality and performance of your Rotadairon® by using only original parts.

- 1 Oil bath filter
- 2 Parking brake lever
- 3 Gearshift
- 4 Hour meter, tachometer
- 5 Seed level indicator
- 6 Seed flow adjustment
- 7 Calibration device
- 8 Pedal for engaging the seed burying rotor
- 9 Seed burying rotor
- 10 Option : Double rear metal mesh roller
- 11 Option : Double rear smooth roller

Machine	SD 700
Seeding width	700 mm (27" 1/2)
Total width	860 mm (33" 3/4)
Front roller type	Metal mesh
Front roller diameter	330 mm (13")
Rear roller type	Smooth
Rear roller diameter	330 mm (13")
Weight	232 Kg (512 lb)
Transport dimension w x L x H	860 mm x 1200 mm x 1310 mm (33" 7/8 x 47" 1/4 x 51" 5/8)
Motorization	
Engine type	Honda thermal gas engine 4.5 HP
Engine air cleaner	Oil bath air cleaner
Transmission	4 forward speeds, 1 reverse
Seeder	
Type of seed drill	Stainless steel gravity seed drill
Seed rate adjustment	Adjustment dial 0 to 6
Seed rate calibration	Calibration bucket
Seed drill capacity	55 liters (14,5 US gal)
Options	- Double rear metal mesh roller - Double rear smooth roller



ROTADAIRON
Départementale 92 - Les Hunaudières
72230 Mulsanne - France
Mail : contacts@rotadairon.fr
Phone number : (33) 2 43 422 422



www.rotadairon.fr